



## Fax Guard 2000

Protection system against remote access



**Fax guard-2000** is a system that can be installed at any facsimile machines on the market with group 3 communication. The system guards that all in and out going information follows the standard protocol for fax communication. If any other unknown protocol or information transmits over the line to the facsimile machine the system break the line to the fax and gives an alarm to the user and lights up the ALARM diode.

When this alarm occurs the system will keep the line open until the operator resets the system with the physical key on the front of the system. The system erase automatically all customer specified codes in the NSF block in the hand shake protocol.

If special codes need to be transmitted in the NSF block these can be installed in the system and then it only will approve this specific NSF codes.

The system is installed between the line and the fax machine. The LINE input shall be connected to the line and the FAX input shall be installed to the fax machine.

To start the guard function turn the physical key so the POWER light diode is light up and the system is ready to guard the fax communication.



FG-2000

## Technical Data

Transmission: .....according to CCITT group 3, T30  
Speeds: ..... 2400, 4800, 7200, 9600 bps  
Communication: ..... fully transparent, no delay  
Display:..... 4 light diodes  
Electrical interface: .....phonenumber

## General Data

Temperature range operating:.....0 to 50 C  
Temperature range storage:..... -20 to 60 C  
Power requirements: ..... 230/115 VAC 50/60Hz  
Size: ..... 80x275x280 mm  
Weight..... 2.4 kg  
Cover..... metal