



SG/FAX-2000

Send Guard for Telefax



The Send Guard for Fax, type SG/FAX-2000, is a complete security system for full control of outgoing fax messages.

The Send Guard controls that the fax message reaches the desired fax machine.

If a non-desired fax machine is reached it will be disconnected before any message leaves the sending fax machine and an acoustical alarm will sound.

The Send Guard is easily installed between the telephone-line and the fax machine or fax modem. It operates with all existing fax machines of group 3 type.

The Send Guard is connected to the sending fax machine only; the receiving fax machine does not need any extra equipment.

The Send Guard automatically learns the connections needed to be controlled.

All fax messages will be clearly marked with the text: Transmission controlled.



SG/FAX-2000

Technical Data:

Communication:.....According to CCITT group 3,T30.
Synchronous speed:.....2400, 4800, 7200, 9600 bit/sek.
Indication of status:.....alfanum. Display 2 x16 characters.
Electrical Interface:.....telephone-line.
Number of controlled fax machines:.....100.

Security Control:

Dialed phone number and received Identification from the actual fax machine on the receiving side are controlled and compared with stored information in the Send Guard

General Data:

Temperature range operating:.....0 to 50 gC.
Temperature range storage:.....-20 to 60 gC.
Power requirements:.....240/115 Volt 50/60Hz.
Dimensions: (H x W x D):.....80x275x280 mm.
Net weight:.....3.0 kg.
Case:.....metal.

Other fax security products:

Automatic fax ID control:.....IDF-2000.
Fax encryption system:.....SLF-2000.
Smart cards:SCA-2000.
Keyloader Stationary:KLS-2000.
Keyloader Portable:KLP-2000.
Fax memory for receiving:MEM-2000.
Fax communication monitoring:.....FDA-96.